

# 389 Swisslon Plus™



- Plush entrance matting with exceptional scraping and unsurpassed water absorbing qualities (5.5 litres per m<sup>2</sup>) for large indoor entrance areas, including wall-to-wall applications and stairs.
- Course yarns provide superb scraping and absorbing of dirt and moisture. Stylish yet subtle chevron pattern or streaked pattern versions hide dirt to maintain their elegant appearance.
- A dense heavyweight vinyl backing ensures longevity.
- Suitable for heavy traffic conditions.
- For placement in recess frames (depth 7 mm) or wall to wall installations in larger entrances at hotels, shopping malls, cinemas, public buildings, department stores, banks, restaurants and on stairs.
- Vacuum/shampooing or use injection/extraction method periodically.

# 389 Swisslon Plus™

| PRODUCT SPECIFICATIONS                     |  |  |
|--|--|--|
| Designation                                | Dust Control Matting   |  |
| Description                                | Absorbent carpet mat   |  |
| Material                                   |  |  |
|  | Top  | Densely tufted cut loop pile (73.340 tufts per m <sup>2</sup> ) consisting of 100% polyamide yarns<br>900 grams of yarn per m <sup>2</sup> |
|  | Backing  | Black vinyl (DOP free)   |
| Process                                    | Tufted   |  |
| Category                                   | Indoor absorbent - Contract  |  |
| Recommended use                            | Indoor - heavy traffic conditions  |  |
| Colours                                    | Wave Charcoal, Wave Red, Wave Taupe, Wave Blue, Wave Grey<br>Twine Charcoal, Twine Red, Twine Taupe, Twine Blue, Twine Grey  |  |
| Weight                                     | 3.5 kg/m <sup>2</sup>  |  |
| Thickness                                  | 8.5 mm   |  |
| Standard sizes                             | 100 cm x 20 m<br>130 cm x 20 m<br>200 cm x 20 m  |  |
| Custom sizes                               | 100 cm, 130 cm and 200 cm per linear meter   |  |
| Special remarks                            |  |  |
| PRODUCT TESTING                            |  |  |
| Tests                                      | Norms  | Results  |
| Abrasion resistance                        | ASTM D3884   |  |
| Colour fastness to light                   | AATCC 16E  | 5  |
| Accelerated wear test by sim floor machine | U.S.   |  |
| Accelerated soiling                        | U.S.   |  |
| Anti-slip                                  | DIN51130<br>BGR181   |  |
| Water retention                            | U.S.   | 5.5 l/m <sup>2</sup>   |
| Sanitary epidemiologic test                | GN 2.1.6.1338-03 MCL<br>GN 2.1.6.2309-07 OBUV  |  |
| Graves tear strength                       |  |  |
| Hardness                                   |  |  |
| Elongation                                 |  |  |
| FIRE TESTING                               |  |  |
|  | Surface Flammability   | ASTM D2859   |
|  | Russian fire retardancy test   |  |
|  | Classification of the reaction to fire performance   | ISO EN 9239<br>Bfl - S1  |
| Sustainability                             | <ul style="list-style-type: none"> <li>• Recyclable material</li> <li>• REACH compliant ( Registration, Evaluation, Authorization and restrictions of Chemicals)</li> <li>• Contributes to cleaner environment by reducing need of cleaning chemicals</li> </ul> |  |